



Millenia Productions, LLC

DBA La Palm Products

3201 N Mead, Wichita, KS 67219

316-425-2500 ph

316-425-2300 fx

www.lapalmproducts.com

Material Safety Data Sheet

Product No. La Palm Platinum Powder
Issue Date (12/01/2009) Review Date (12/01/2019)

Section 1: Product and Company Identification

Product Name: La Palm Platinum Resin (Powder)

Synonym: Micro-Bed Resin(Powder)

Company Name

Millinea Productions

Emergency Number 1-800-424-9300 24 hrs a day.

Section 2: Composition / Information on Ingredients

Principle Hazardous Component(s) (chemical and common name(s)) (Cas. No)	%	OSHA PEL mg/m3	ACGIH TLV mg/m3	NTP	IARC	OSHA regulated
N-Butyl Methacrylate (97-88-1)	ND	None	None	ND	ND	ND
Styrene Monomer (100-42-5)	ND	100ppm	50ppm	ND	ND	ND
Hydroxy Propyl Methacrylate (27813-02-1)	ND	None	None	ND	ND	ND
Glycol Methacrylate 868-77-9	ND	NE	NE	ND	ND	ND

Section 3: Hazard Identification

Emergency overview

Appearance: Powder with a Ester odor.

Immediate effects: Non Skin allergy.

Potential health effects

Primary Routes of entry: Skin contact, eye contact, and inhalation.

Signs and Symptoms of Overexposure: Allergic reaction on the skin. Eyes: Irritation

Skin: Non – Moderate Irritation to skin if prolonged contact.

Ingestion: Material may be harmful if swallowed.

Inhalation: NA.

Chronic Exposure: None known

Chemical Listed As Carcinogen Or Potential Carcinogen: No

See Toxicological Information (Section 11)

Potential environmental effects

See Ecological Information (Section 12)

Section 4: First Aid Measures

If accidental overexposure is suspected

Eye(s) Contact: Flush eyes with large amounts of water for at least 15 minutes. Consult physician if irritation persists.

Skin Contact: Wash affected skin area with soap and water.

Inhalation: Move subject to fresh air. .

Ingestion: ND

Note to physician

Treatment: ND

Medical Conditions generally Aggravated by Exposure:

Section 5: Fire Fighting Measures

Flash Point: 64°F

Flammable Limits: LEL Lower 2%; UEL Upper 8%

Auto-ignition point: 294°C / 561°F

Fire Extinguishing Media: CO₂, dry chemical, water spray.

Special Fire Fighting Procedures: Do not enter fire area without proper protection. Fight fire from safe distance (protected location). Heat / impurities may increase temperature /build pressure/ rupture closed containers, spreading fire, increasing risk of burns/ injuries. Water may be ineffective in fire fighting due to low solubility. Use water spray or fog for cooling. Pressure relief system may plug with solids, increasing risk of overpressure. Notify authorities if liquid enters sewer or public waters.

Unusual Fire and Explosion Hazards: Heat can cause polymerization. Heated containers can explode. Vapors can travel to a source of ignition and flash back.

Hazardous combustion products: ND

DOT Class: Non Flammable

Section 6: Accidental Release Measures.

Section 7: Handling and Storage

Precautions to be Taken in Handling and Storage: Store out of direct sunlight in a cool place. Do not store near radiators, steam pipes and other sources of heat. Do not store under oxygen-free atmosphere. Leave air space over liquid surface in all containers; introduce air periodically if stored more than 6 months. Use material within 3 year of retest for stability.

Section 8: Exposure Controls / Personal Protection **Engineering Controls**

Ventilation required: Use local exhaust ventilation with a minimum capture velocity of 100 ft/min. (30m/min.) at the point of vapor evolution. Refer to the current edition of INDUSTRIAL VENTILATION: A Manual of Recommended Practice published by the American Conference of Governmental Industrial hygienists for information on the design, installation, use and maintenance of exhaust systems.

Personal Protection Equipment

. Rinse hands skin after use. Wash your hands with soap and water. .

Skin protection: Use chemically resistant apron or other impervious clothing to avoid prolonged or repeated skin contact.

Eye protection: Keep away from direct contact with eyes.

Section 9 Physical and Chemical Properties

Appearance and Physical State: Powder.

Odor (threshold): Ester odor.

Specific Gravity (H₂O=1): NA

Vapor Pressure (mm Hg): ND

Vapor Density (air=1): ND

Percent Volatile by volume: ND

Evaporation Rate (butyl acetate=1):

Boiling Point: 60°C / 140°F

Freezing point / melting point: ND

pH: ND

Solubility in Water: Negligible

Molecular Weight: ND

Section 10: Stability and Reactivity

Stability: This material is considered stable under specified conditions of storage, shipment and/or use. MEQH is added as a polymer inhibitor.

Conditions to Avoid: Avoid heat, oxygen-free atmosphere.

Materials to Avoid (Incompatibility): Strong Acids, bases, oxidizing agents, reducing agents..

Hazardous Decomposition Products: There are no known hazardous decomposition products for this material.

Non Hazardous Polymerization: May occur if direct Sunlight for multiple months.

Section 11: Toxicological Information

Results of component toxicity test performed: Oral LD50-Rat >5000mg/kg.

Human experience: ND

This product **does not** contain any compounds listed by NTP or IARC or regulated by OSHA as a carcinogen.

Section 12: Ecological Information

Ecological Information: ND

Chemical Fate Information: ND

Section 13 Disposal Considerations

RCRA 40 CFR 261 Classification: ND

Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal.

Section 14: Transportation Information

US DOT Information: Proper shipping name: (Monomer, methacrylate ester, mixture)

Hazard Class: 3

Packaging group: II

UN Number: UN1993

IATA: Proper shipping name:

Hazard Class: 3

Packing group: II

Section 15: Regulatory Information

United States Federal Regulations

MSDS complies with OSHA's Hazard Communication Rule 29, CFR 1910.1200.

SARA: ND

SARA Title III: ND

RCRA: ND
TSCA: ND
CERCLA: ND

State Regulations

California Proposition 65: No

International Regulations

Canada WHMIS: ND
Europe EINECS Numbers: ND

Section 16: Other Information

Label Information: ND
European Risk and Safety Phrases: ND
European symbols needed: ND
Canadian WHMIS Symbols: ND
Hazard Rating: Health: ND; Fire: ND; Reactivity: ND
(0=least, 1=Slight, 2=Moderate, 3=High, 4=Extreme)

Abbreviations used in this document

NE= Not established
NA= Not applicable
NIF= No Information Found
ND= No Data

The above information is based on data available to us and is believed to be correct. However no warranty, merchantability, fitness for any use or any other warranty is expressed or to be implied regarding the accuracy of these data, the result to be obtained from the use thereof, the hazards connected with the use of the material, or that any such use will not infringe any patent. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility resulting from its use. This information is furnished upon the condition that the person receiving it shall make his own determination for the suitability of the material for his particular purpose.
